
Surrey County Council Highway Safety Inspection Policy Identification of defect severity

Carriageway inspections

Table 1: This table shows the type of carriageway inspections which are carried out with the description of defect and it's priority

Туре	Description	Priority
Pothole	Cycle lanes	P2
As a general rule, the diameter, at the surface	> 25mm in marked cycle lanes and at	
level, should be >75mm on cycle lanes and	recognised crossing points (normally in	
>150mm on carriageways	town centre situations	
Pothole	All other locations	P2
As a general rule, the diameter, at the surface	> 40mm at all other locations	
level, should be >75mm on cycle lanes and		
>150mm on carriageways		
Pothole	Cycle lanes	P3
As a general rule, the diameter, at the surface	Approaching 25mm, with likelihood of	
level, should be >75mm on cycle lanes and	worsening in short	
>150mm on carriageways	term. Advanced local crazing likely to	
	pothole	
Pothole	All other locations	
As a general rule, the diameter, at the surface	Approaching 40mm, with likelihood of	
level, should be >75mm on cycle lanes and	worsening in short	
>150mm on carriageways		



Response categoriesTable 4: This table shows the types of response categories and a description showing the timescale for repair.

Response Category	Description
P2 (Safety Priority 2)	Correct/repair or make safe within 5 working days. If it is not possible to permanently correct/repair defect within 5 working days, a permanent repair should be carried out within 20 working days, where appropriate, i.e. unless maintenance/improvement works are planned within a timescale not exceeding 6 months. This timescale should be appropriate to the defect type, location road/footway classification and usage.
P3 (Safety Priority 3)	A permanent repair should be carried out within 20 working days where appropriate, i.e. unless maintenance/improvement works are planned within a timescale not exceeding 6 months. This timescale should be appropriate to the defect type, location road/footway classification and usage.